

511 Seal & Enhance

Impregnating Color Enhancer

Ready to Use "One Step" Solvent Base Penetrating/Color Enhancer for All Honed, Textured and Polished Stone & Tile Surfaces Including:

- | | | |
|-----------|----------------------------|-----------------|
| ■ Granite | ■ Marble | ■ Natural Stone |
| ■ Slate | ■ Limestone | ■ Quarry Tile |
| ■ Grout | ■ Not for Concrete/Masonry | |

Special Features

- | | |
|-------------------------------------|------------------------------|
| ■ Superior Stain Protection | ■ Superior Color Enhancement |
| ■ Oil Resistant | ■ Water Resistant |
| ■ One Product, One Step | ■ Durable |
| ■ Easy-to-Use | ■ Grout Release |
| ■ Interior & Exterior Applications | ■ Non Yellowing |
| ■ Color Enhancing Grout Sealer | |
| ■ Revives Color to Washed Out Grout | |

Product Description

KEEP OUT OF REACH OF CHILDREN. **511 Seal & Enhance** is a unique, one-step formula designed for maximum stain protection and superior color enhancement. **511 Seal & Enhance** penetrates into the surface & forms an invisible barrier that is resistant to moisture & stains, while allowing vapor to escape. It will enhance the color of tumbled, honed, acid-washed, saandblasted, flamed, textured and polished natural stone, brick, grout & clay pavers. **511 Seal & Enhance** can also be used on new installations as a grout release before the grouting process.

Sample Testing

Due to variations between substrates, sample testing is recommended to assure maximum performance and suitability for the intended use. Once enhanced, stone cannot be restored to its original color. **Users must determine the suitability of the product for their intended use.**

NEW INSTALLATIONS

Read entire label and SDS/PDS before using. **511 Seal & Enhance** should not be diluted or thinned in any way. **511 Seal & Enhance** should be used as directed from approved container.

Follow the recommended installation methods and procedures of the Marble Institute of America, Building Stone Institute and the Tile Council of America. Allow new setting materials and grout to cure per manufacturers instructions prior to sealing.

Sealing as a Grout Release

To insure the best possible installation, **511 Seal & Enhance** should be applied as a grout release before the grouting process. **511 Seal & Enhance** will resist dye absorption, facilitate grout residue removal (up to 45% faster), and offer superior stain resistance during and after the construction process.

Directions

1. Protect neighboring and adjacent surfaces including baseboards, wood, carpet, metal and landscaping.
2. Sweep or vacuum all dust, dirt and surface debris.
3. Insure the surface is clean, dry and free from contaminants.
4. Liberally apply an even application of **511 Seal & Enhance** using a **Miracle Sealants' Mira Brush**, clean white towel or natural fiber paint brush. Be careful not to allow sealants into open un-grouted joints.
5. Allow **511 Seal & Enhance** to penetrate the surface for 3 - 5 minutes before removing all excess product before it dries on the surface with a clean towel.
6. A 2nd application is necessary and should be applied after the first has dried at least 1 hour.

7. Any excess product residue that may dry on the surface can be removed by reapplying product and wiping excess off immediately while wet, with a white terry cloth towel. Allow to cure 6 - 12 hours before grouting.
8. Proceed with the grouting process per the manufacturer's instructions.
9. Clean all excess grout completely from the surface with a clean sponge and water. Take the time at this stage of the installation to carefully clean and detail.
10. Allow grout joints to dry per manufacturers specification.
11. If grout clean up is not performed effectively, additional cleaning may be necessary.

Grout Sealing

Once the grout has cured per the manufacturers recommendations, proceed with the sealing of the grout.

Directions

1. Insure that the surface is clean, dry and free from contaminants.
2. Liberally apply an even application of **511 Seal & Enhance** using a **Miracle Sealants' Mira Brush**, clean white towel or a natural fiber paint brush directly to untreated grout joints.
3. Allow **511 Seal & Enhance** to penetrate the surface for 3 - 5 minutes before removing all excess product with a clean towel.
12. A 2nd application is necessary and should be applied after the first has dried at least 1 hour.
13. Any excess product residue that may dry on the surface can be removed by reapplying product and wiping excess off immediately while wet, with a white terry cloth towel. Allow to cure 6 - 12 hours before grouting.

Finished area should be allowed to cure for 12 - 24 hours before putting into service. For optimum results keep area dry and free from stains for 72 hours after application.

EXISTING INSTALLATIONS

Surface must be dry and free of contaminants including previously applied sealers, coatings, waxes, dirt, lime & hard water deposits, efflorescence, rust and other heavy dirt and grime.

Floor Finish Removal

To remove existing floor finish and/or waxes use **Mira Strip** for solvent base finish and **Finish Sealer Stripper** for water base finish as directed.

Heavy Duty Cleaning

To remove lime, hard water deposits, efflorescence rust and other heavy dirt and grime use **HDAC (Heavy Duty Acidic Cleaner)** "Stronger" or **Phosphoric Acid Cleaner** "Mild-Strong" as directed. These acid cleaners can affect the surface finish of acid sensitive stone and tile. For acid sensitive stone or tile use **Liquid Poultice** as directed.

Slip Resistance

511 Seal & Enhance increases the static coefficient of friction on all surfaces. **511 Seal & Enhance** has been used successfully for compliance with the American Disability Act's recommendations for slip resistance (ASTM C 1028-89) on polished & honed surfaces.

Protect Neighboring Surfaces

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non masonry surfaces.

Light Cleaning

For light cleaning use **Tile & Stone Cleaner** as directed.

Sealing (Surface & Grout)

Follow the application instructions previously mentioned, except now seal grout joints at the same time as the rest of the stone or tile surface. When treating the surface and grout at the same time make sure to saturate the grout with **511 Seal & Enhance**. Do not allow **511 Seal & Enhance** to puddle on the surface.

Coverage

Coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution is left on the surface and application methods. Used as directed, **511 Seal & Enhance** will cover approximately 250 - 2,000 square feet per gallon (25 - 200 square meters per 3.785 liters).

RESEALING

Resealing will vary depending on porosity, density, hardness, foot traffic and the elements (indoor or outdoor) the area is exposed to. As a general rule, medium to dense surfaces exposed to heavy foot traffic can be resealed every 1 - 3 years. Very hard surfaces exposed to heavy foot traffic can be resealed every 3 - 5 years. It is important to remember that any additional or future applications of **511 Sealants** will require approximately half the amount of sealant as originally used.

Storage

Store **511 Seal & Enhance** in the original container, properly sealed to avoid contamination and evaporation. When store in the upright position at 77° F (25° C), **511 Seal & Enhance** will have a shelf life of 12 months. Do not allow to freeze.

Technical Support

For additional technical support, contact Miracle Sealants Company @ 1-800-350-1901 or 626-443-6433 ext. 3013.
Monday – Friday from 6:30 am – 5:00 pm PT.

Office Hours

Monday – Friday from 8:30 am – 5:00 pm PT.
1-626-443-6433 • 1-800-350-1901 Fax: 1-626-443-1435

Website

www.miraclesealants.com

Product Damage

If product is damaged during transportation contact
Info Trac @ 1-800-535-5053

Additional Products

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaners, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it-yourself specialist.

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven defective. **Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.** Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

Caution

511 Seal & Enhance contains combustible petroleum distillates. All solvents must be considered toxic and must be used in a well-ventilated area. Good ventilation means that fresh air is flowing in such a way as to feel a slight breeze. Open windows and use fans to circulate air. Continue to ventilate until vapors are eliminated. Exposure to high vapor concentration must be avoided. Inhaling the vapors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Gloves should be worn at all times. Keep small children and pets out of the area until product or surface has thoroughly dried. Refer to the MSDS for additional information.

Safety Data Sheet



1. Identification

Product Name:	MS 511 SEAL AND ENHANCE GAL 4PK	Revision Date:	2/24/2020
Product Identifier:	SEENGAL4	Supersedes Date:	5/14/2019
Recommended Use:	One-Step Sealer & Enhancer		
Supplier:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
Preparer:	Regulatory Department		
Emergency Telephone:	24 Hour Hotline: 847-367-7700		

2. Hazard Identification

Classification

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

11% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapor.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Aspiration Hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2A	H319	Causes serious eye irritation.

GHS LABEL PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. NO SMOKING.
P233	Keep container tightly closed.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370+P378	In case of fire: Use alcohol film forming foam, carbon dioxide, dry chemical, dry sand to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local, regional and national regulations.
P201	Obtain special instructions before use.
P308+P313	IF exposed or concerned: Get medical advice/attention.

P405	Store locked up.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331	Do NOT induce vomiting.
P264	Wash hands thoroughly after handling.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P321	For specific treatment see label.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.

GHS SDS PRECAUTIONARY STATEMENTS

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

3. Composition / Information On Ingredients

HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt.% Range</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Hydrotreated Light Distillate	64742-47-8	25-50	GHS08	H304
Naphtha, Hydrotreated Heavy	64742-48-9	2.5-10	GHS08	H304
Xylenes (o-, m-, p- Isomers)	1330-20-7	2.5-10	GHS02-GHS07	H226-315-319-332
n-Butyl Acetate	123-86-4	1.0-2.5	GHS02-GHS07	H226-336
3-Aminopropyltriethoxysilane	919-30-2	1.0-2.5	GHS05-GHS06	H302-314-331
Ethylbenzene	100-41-4	0.1-1.0	GHS02-GHS07-GHS08	H225-304-332-351-373
Stannane, dioctylbis[(1-oxododecyl)oxy]-	3648-18-8	0.1-1.0	Not Available	Not Available

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, get medical attention.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: No unusual fire or explosion hazards noted. Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Combustible liquid and vapor.

SPECIAL FIREFIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

Special Fire and Explosion Hazard (Combustible Dust): No Information

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Avoid excess heat.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Hydrotreated Light Distillate	64742-47-8	50.0	N.E.	N.E.	N.E.	N.E.
Naphtha, Hydrotreated Heavy	64742-48-9	10.0	N.E.	N.E.	N.E.	N.E.
Xylenes (o-, m-, p- Isomers)	1330-20-7	5.0	100 ppm	150 ppm	100 ppm	N.E.
n-Butyl Acetate	123-86-4	5.0	50 ppm	150 ppm	150 ppm	N.E.
3-Aminopropyltriethoxysilane	919-30-2	5.0	N.E.	N.E.	N.E.	N.E.
Ethylbenzene	100-41-4	1.0	20 ppm	N.E.	100 ppm	N.E.
Stannane, dioctylbis[(1-oxododecyl)oxy]-	3648-18-8	1.0	0.1 mg/m3	0.2 mg/m3	0.1 mg/m3	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Solvent Like	Odor Threshold:	N.E.
Specific Gravity:	0.881	pH:	N.A.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Slight	Partition Coefficient, n-octanol/ water:	N.D.
Decomposition Temp., °C:	N.D.	Explosive Limits, vol%:	0.7 - 17.5
Boiling Range, °C:	82 - 537	Flash Point, °C:	42
Flammability:	Supports Combustion	Auto-ignition Temp., °C:	N.D.
Evaporation Rate:	Slower than Ether	Vapor Pressure:	N.D.
Vapor Density:	Heavier than Air		

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: No Information

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Substance causes moderate eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Irritating to the nose, throat and respiratory tract. Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: IARC lists Ethylbenzene as a possible human carcinogen (group 2B). Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-47-8	Hydrotreated Light Distillate	>5000 mg/kg Rat	>2000 mg/kg Rabbit	>5000 mg/L Rat
64742-48-9	Naphtha, Hydrotreated Heavy	>6000 mg/kg Rat	>3160 mg/kg Rabbit	N.E.
1330-20-7	Xylenes (o-, m-, p- Isomers)	3500 mg/kg Rat	>4350 mg/kg Rabbit	29.08 mg/L Rat
123-86-4	n-Butyl Acetate	10768 mg/kg Rat	>17600 mg/kg Rabbit	> 21 mg/L Rat
919-30-2	3-Aminopropyltriethoxysilane	1780 mg/kg Rat	4290 mg/kg Rabbit	>7.35 mg/L Rat
100-41-4	Ethylbenzene	3500 mg/kg Rat	15400 mg/kg Rabbit	17.4 mg/L Rat
3648-18-8	Stannane, dioctylbis[(1-oxododecyl)oxy]-	6450 mg/kg Rat	N.E.	N.E.

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Do not incinerate closed containers. Dispose of material in accordance to local, state, and federal regulations and ordinances.

14. Transport Information

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>TDG (Canada)</u>
UN Number:	N.A.	1263	1263	N.A.
Proper Shipping Name:	Not Regulated	Paint	Paint	Not Regulated
Hazard Class:	N.A.	3	3	N.A.
Packing Group:	N.A.	III	III	N.A.
Limited Quantity:	No	Yes, >5L No	Yes, >5L No	No

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Skin Corrosion or Irritation, Serious eye damage or eye irritation, Aspiration Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Xylenes (o-, m-, p- Isomers)	1330-20-7
Ethylbenzene	100-41-4

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations:

California Proposition 65:

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

16. Other Information**HMIS RATINGS**

Health: 2* Flammability: 2 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 2 Instability: 0

Volatile Organic Compounds 580 g/L

SDS REVISION DATE: 2/24/2020

REASON FOR REVISION: Revision Description Changed
Product Composition Changed
Substance and/or Product Properties Changed in Section(s):
01 - Identification
02 - Hazard Identification
09 - Physical & Chemical Properties
14 - Transport Information
16 - Other Information
Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.