

RLA MS TIMBER FLOORING ADHESIVE

Solvent & Isocyanate Free



PRODUCT DESCRIPTION:

RLA MS Timber Flooring Adhesive is a single-part, permanently flexible solvent and isocyanate free MS timber flooring adhesive.

FEATURES AND BENEFITS:

- Non Flammable.
- Green Star Compliant
- Green TAG Certified
- Solvent & Isocyanate free.
- Will not re-emulsify with water contact.
- Stands up well under trowel
- Easy to Apply

FOR BONDING:

MS Timber Flooring Adhesive is recommended for bonding, Solid Timber Flooring, Parquet Flooring and Engineered Timber Flooring to Concrete and Timber Substrates. MS Timber Flooring Adhesive is also recommended for bonding approved acoustic underlays to most common subfloors.

SURFACE PREPARATION:

Subfloors must be dry, sound, smooth, clean and in accordance with the relevant Floorcoverings Australian Standards.

Subfloors must also be free of wax, grease, oil, polishes, old adhesive, curing compounds, high levels of moisture and any other surface contaminants that may affect adhesion. If mechanical preparation is required prepare the floor using recommended preparation methods such as shot blasting, scarifying, diamond grinding, to provide a roughened, clean, sound, solid and open porous surface.

It is recommended that highly absorbent concrete subfloors be primed with RLA PU 95 Vapour Barrier prior to the application of adhesive. The minimum subfloor temperature before commencing installation should be 10°C Do not use solvents, or acid etching to clean the subfloor. All concrete subfloors must be tested for moisture content. Relative humidity readings should be determined as per ASTM F2170. Ensure the relative humidity (RH) is below 85% (tested as per ASTM F2170 insitu probe method). If the RH of the sub-floor is above 85% we recommended the use of RLA Two Part Epoxy Moisture Barrier or RLA Single Part Polyurethane Vapour Barrier. The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C. Indentations and uneven concrete subfloors should be treated with the RLA range of levelling compounds and be in accordance with manufacturer's recommendations. Where temperatures are less than 10°C or greater than 30°C are encountered, contact our technical staff for advice.

MOISTURE PROTECTION:

Concrete slabs can be a source of excess moisture. To prevent moisture migration, apply Two coats RLA Two Part Epoxy Moisture Barrier ensuring the second coat is applied perpendicular to the direction of application of the first coat. Alternatively RLA PU 95 Single Part Polyurethane Vapour Barrier. Application of Timber Flooring Adhesive onto RLA Moisture or Vapour Barrier. Ensure the adhesive is applied onto the Moisture Barrier within 4 days after the application of Moisture Barrier has taken place and cured. Ensure the Barrier is clean and free from dirt, dust and any other contaminant that may affect adhesion. Please refer to the Product Data Sheets for further information and application instructions .

CONCRETE SUBSTRATES:

Subfloors must be dry, sound, smooth, clean, any contaminants that may affect adhesion and in accordance with the relevant Floorcoverings Australian Standards. All concrete subfloors must be tested for moisture content before the application adhesive, primers and barriers.

Indentations and uneven concrete subfloors should be treated with the RLA range of levelling compounds and be in accordance with manufacturer's recommendations.

TIMBER SUBSTRATES:

Timber flooring must be solid, sound, clean and free from wax, oil, free from gaps and securely fixed and in accordance with the Timber Flooring Manufactures Instructions and relevant Australian Standards.

Timber Flooring may be coated with a resin waterproof protective layer.

This layer can act as a bond breaker and can affect adhesion to applied finishes, it should be removed by sanding the subfloor before application of timber flooring underlayment.

It is recommended for the Installation of timber flooring onto timber substrates, Timber Flooring is nailed/secretly fixed in combination with application of adhesive.

Please ensure adequate cross-flow ventilation and that the minimum height clearance between earth and the timber flooring is in accordance with the relevant Australian Standards. Failure to have adequate ventilation can result moisture build up under the subfloor and can compromise the installation of underlayment and Floorcoverings.

APPLICATION:**BONDING ACOUSTIC UNDERLAY TO THE SUB-FLOOR:**

Apply the adhesive evenly with a 2-3mm V notched trowel (2-3mm notched trowel dependant on underlay type) at a rate of approx. 2 m² per litre. Please refer to the underlay or timber manufacturer's instructions for specific trowel size. Install the underlay into the wet adhesive film and ensure transfer occurs between the adhesive film and the underlay. Roll the underlay with a suitable roller to ensure a minimum 100% transfer rate of adhesive film is achieved between the underlay and subfloor. Allow the adhesive to dry for 24 hours prior to installing the floor-covering.

BONDING TIMBER FLOORING SYSTEMS TO ACOUSTIC UNDERLAY:

Apply adhesive evenly with a 3-5mm V notched trowel - please refer to the timber manufacturer's instructions for specific trowel size at a rate of approx. 1 – 1.2 m² per litre. Install the timber flooring into the wet film of adhesive and ensure transfer occurs between the adhesive film and the timber flooring. A minimum of 100% (Transfer) contact between the underlay and timber flooring is required and maintain full contact with adhesive until full cure is achieved. For best results timber flooring should be installed within 30 minutes of the adhesives application.

CONCRETE & CEMENTITIOUS SUBSTRATES:

Subfloors must be dry, sound, smooth, clean, any contaminants that may affect adhesion and in accordance with the relevant Floorcoverings Australian Standards. Apply adhesive evenly with a 4-5mm V notched trowel - please refer to the timber manufacturer's instructions for specific trowel size at a

Version: 1.0

Issue date: 30/08/2023

RLA Polymers Pty Ltd ACN 004 709 915

Head Office
215 Colchester Road
Kilsyth, Victoria, 3137
Tel: 1800 242 931

New South Wales
363 Wentworth Ave
Pendle Hill, N.S.W, 2145

Queensland
57 Fulcrum Street
Richlands, QLD, 4077

South Australia
Unit 2/7 Berger Road
Wingfield, SA, 5013

Western Australia
24 Hanwell Way
Bassendean, W.A, 6054
Tel: 08 9279 8911

rate of approx. 1 – 1.2 m² per litre. Install the timber flooring into the wet film of adhesive and ensure transfer occurs between the adhesive film and the timber flooring. A minimum of 100% (Transfer) contact between the substrate and timber flooring is required and maintain full contact with adhesive until full cure is achieved. For best results timber flooring should be installed within 30 minutes of the adhesives application.

TIMBER FLOORING SUBSTRATES:

Subfloors must be dry, sound, smooth, clean, any contaminants that may affect adhesion and in accordance with the relevant Floorcoverings Australian Standards. Apply adhesive evenly with a 4-5mm V notched trowel - please refer to the timber manufacturer's instructions for specific trowel size at a rate of approx. 1 – 1.2 m² per litre. Install the timber flooring into the wet film of adhesive and ensure transfer occurs between the adhesive film and the timber flooring. A minimum of 100% (Transfer) contact between the substrate and timber flooring is required and maintain full contact with adhesive until full cure is achieved. Do not allow heavy traffic for 24 hours. Sanding can commence 3 to 7 days after the completion of the entire installation. Please note: Sanding times may vary due to climatic conditions please check with the manufacture.

CURE TIME:

Cure times can vary substantially and are dependent on weather conditions such as temperature and humidity. Typically, MS will form a firm skin in two hours and cure in approximately 24 hours. Hotter and more humid conditions will increase the rate of cure and decrease the skin time, whereas colder climates and lower humidity will decrease cure times and increase skin times

CLEAN UP:

Clean tools and equipment immediately after use with a suitable solvent such as white spirits or alternatively Citrus based RLA Handy Wipes. Cured MS Timber Flooring Adhesive can be removed by mechanical means or with RLA Handy Wipes.

COVERAGE:

2-3mm V notched trowel notched trowel will achieve approximately 2 square metres per litre. 4-5mm V notched trowel notched trowel will achieve approximately 1-1.5 square metres per litre

CONTAINER SIZES:

10 litre/ 15kg containers and 600 gram sausages

SHELF LIFE / STORAGE:

12 months when stored in original unopened packaging
To be stored in a dry area off the ground.

SAFETY & HANDLING:

A Safety Data Sheet is available on request.
Product is classified as NON-DANGEROUS GOODS.
According to the WHS Regulations and the ADG Code.

First Aid:

In use, please ensure that Occupational Health and Safety requirements are observed.
Eyes: Irrigate with water for 10 minutes and see a doctor.
Skin: Wash off with warm water and soap.
If swallowed, give plenty of water. Do not induce vomiting. Seek medical attention.

Version: 1.0

Issue date: 30/08/2023

RLA Polymers Pty Ltd ACN 004 709 915

Head Office
215 Colchester Road
Kilsyth, Victoria, 3137
Tel: 1800 242 931

New South Wales
363 Wentworth Ave
Pendle Hill, N.S.W, 2145

Queensland
57 Fulcrum Street
Richlands, QLD, 4077

South Australia
Unit 2/7 Berger Road
Wingfield, SA, 5013

Western Australia
24 Hanwell Way
Bassendean, W.A, 6054
Tel: 08 9279 8911

PRECAUTIONS:

- Please ensure timber flooring is placed into the Wet Film of adhesive and apply sufficient pressure to ensure transfer occurs between the adhesive film and floorcovering.
- A minimum of 100% (Transfer) contact between the substrate and the back of each individual piece of timber is required and maintain full contact with adhesive until full cure is achieved after a minimum of 24 hours (mechanical fixing or weighing down is recommended)
- Application of Timber Flooring Adhesive directly onto RLA Moisture or Vapour barrier ensure the adhesive is applied onto the Moisture Barrier within 4 days after the application of Moisture Barrier has taken place and cured.
- Do not walk on laid matting during the first four hours after installation. Avoid air entrapment when making the bond or filling joints. For application details of timber flooring systems, contact the timber flooring Page 4 of 5 manufacturer. Care should be taken to prevent any reaction or damage pre finished timber coatings.
- Do not use adhesive in excessive hot or cold conditions i.e. below 10°C or above 30°C
- This adhesive will not stand up to hydrostatic pressure or capillary action.
- Ensure your trowel is notched to the manufacturer's recommendations at all times.
- Timber flooring systems must be acclimatised, refer to the timber flooring manufacturers recommendations, prior to the use of this adhesive.
- If in doubt regarding suitability of adhesive, always contact the manufacturer.
- Always follow manufacturer's instructions.
- Do not apply over acrylic or PVA primers/sealers.
- Not recommended to be used in totally confined spaces as requires atmospheric moisture to cure properly.
- Do not expose to water or alcohol based cleaners before full cure.

- Must be fully cured before sanding, allow a minimum of 72 hours.
- Compatibility tests must be first carried out. Due to many forms of timber flooring available today, preliminary adhesion testing should be undertaken by the installer to confirm adhesion. RLA Polymers can assist on large projects.
- Do not apply over dense burnished concrete surfaces without abrading first to obtain a mechanical key for the adhesive to bond to.

WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification. We certify that when fully cured this product is suitable for use and will perform as described in our technical data sheet or other published materials. RLA Polymers will replace product free of charge when purchased from any legally verifiable source, and where product is proven to have been stored, handled and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with the relevant Australian Standard and the Floorcovering Manufacturers instructions and the floorcoverings must have been subject to normal traffic conditions. Warranty doesn't not apply if damage, loss, failure to follow instructions or other circumstances are out of our control. Sufficient time and access to investigate any complaint must be accorded to RLA Polymers. The consumer is responsible for any expenses incurred in making a claim. A claim form can be requested by:
Phone: 1800 242 931
Email: info@rlapolymers.com.au
Mail: 215 Colchester Road Kilsyth Victoria 3137 (attention Customer Service)

Version: 1.0

Issue date: 30/08/2023

RLA Polymers Pty Ltd ACN 004 709 915

Head Office
215 Colchester Road
Kilsyth, Victoria, 3137
Tel: 1800 242 931

New South Wales
363 Wentworth Ave
Pendle Hill, N.S.W, 2145

Queensland
57 Fulcrum Street
Richlands, QLD, 4077

South Australia
Unit 2/7 Berger Road
Wingfield ,SA, 5013

Western Australia
24 Hanwell Way
Bassendean, W.A, 6054
Tel: 08 9279 8911

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Issued: July 2023

Version: 1.0

Issue date: 30/08/2023

RLA Polymers Pty Ltd ACN 004 709 915

Head Office
215 Colchester Road
Kilsyth, Victoria, 3137
Tel: 1800 242 931

New South Wales
363 Wentworth Ave
Pendle Hill, N.S.W, 2145

Queensland
57 Fulcrum Street
Richlands, QLD, 4077

South Australia
Unit 2/7 Berger Road
Wingfield ,SA, 5013

Western Australia
24 Hanwell Way
Bassendean, W.A, 6054
Tel: 08 9279 8911

Safety Data Sheet



NON-Hazardous, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: RLA MS Timber Flooring Adhesive

Recommended use: used for home decoration and construction works.
Use according to manufacturer's directions.

Supplier: RLA Polymers Pty Ltd
ABN: 89 004 709 915
Street Address: 215 Colchester Road
Kilsyth VIC 3137
Telephone: 1800 242 931

Emergency Telephone number: 1800 033 111 (all hours)

2. HAZARDS IDENTIFICATION

Based on available information, this material is not classified as hazardous according to criteria of Safe Work Australia GHS 7.

Poison Schedule: Not Applicable

DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	1-5 %
Trimethoxyvinylsilane	2768-02-7	1-5 %
Ingredients determined to be Non-Hazardous		Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink.

Safety Data Sheet



Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders: Wear rubber boots, overalls, gloves, chemical goggles. Available information suggests that gloves made from butyl rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Non-combustible material.

Fire fighting further advice: Not applicable.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Calcium carbonate (a)	-	10	-	-	-

Safety Data Sheet



As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator.

Personal Protection Equipment: RUBBER BOOTS, OVERALLS, GLOVES, CHEMICAL GOGGLES.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear rubber boots, overalls, gloves, chemical goggles. Available information suggests that gloves made from butyl rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Base Units: Litres
Form: Liquid
Colour: Brown
Odour: Weak

Specific Gravity: Not available
Flash Point (°C): >70
Boiling Point/Range (°C): N Av
pH: N Av
Viscosity: N Av

(Typical values only - consult specification sheet)
N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Safety Data Sheet



Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin may result in irritation.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: May be an eye irritant.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): $LC_{50} > 20.0$ mg/L for vapours or $LC_{50} > 5.0$ mg/L for dust and mist.

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000$ mg/Kg bw

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000$ mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as not a specific hazard to target organs by a single exposure.

Chronic Toxicity

Mutagenicity: This material has been classified as not a mutagen.

Carcinogenicity: This material has been classified as not a carcinogen.

Reproductive toxicity (including via lactation): This material has been classified as not a reproductive toxicant.

Specific target organ toxicity (repeat exposure): This material has been classified as not a specific hazard to target organs by repeat exposure.

12. ECOLOGICAL INFORMATION

Product Name: RLA MS Timber Flooring Adhesive

Reference No: 620650

Issued: 2024-04-24

Version: 2.1.1.3

Page 4 of 6

Safety Data Sheet



Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Long-term aquatic hazard: This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log K_{ow} < 4.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): Not Applicable.

16. OTHER INFORMATION

Safety Data Sheet



Reason for issue: Product name change

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.